

SCM300ASL PRO: 3-way active*



Features

- 34mm soft dome tweeter.
- Twin full spec "SL" 15"/375mm bass drivers.
- ATC 75mm "Super Dome" mid driver.
- Rack-mount ATC 4 way grounded plane 850W amplifier.
- Clip indication.
- 6 year warranty.

Specifications

Drivers : HF 34mm, Mid 75mm, LF 2 x 375mm

Amplitude Linearity (± 2 dB) : 50Hz-12kHz

Cut-off Frequencies (-6 dB) : 25Hz, 20kHz (free standing) 20Hz, 20kHz (soffit mounted)

Horizontal Dispersion : $\pm 80^\circ$, Coherent

Vertical Dispersion : $\pm 10^\circ$, Coherent

Max. Continuous SPL (1 metre) : 121dB

Crossover Frequencies : 380Hz, 3.5kHz

Input Connectors : Male XLR

Input Sensitivity : 2V

Input Impedance : Balanced $> 10k\Omega$

Amplifier Output : Bass 275+275W, Mid 200W, High 100W

Filters : Even Order Critically Damped

Overload Protection : Active FET momentary gain reduction plus thermal tweeter protection

Front Panel Indicators : Power On indicator, Gain Reduction warning

Dimensions (HxWxD) : 884 x 925 x 460mm (34.8" x 36.4" x 18.7")

Weight : 140kg / 308lbs

*Passive versions available.



Loudspeaker Technology Ltd

Gypsy Lane, Aston Down, Stroud, Gloucestershire GL6 8HR United Kingdom

Telephone 01285 760561 Fax 01285 760683

Email info@atc.gb.net Website www.atcloudspeakers.co.uk

ATC reserves the right to vary products and specifications without prior notice.